

PRODUCT RANGE

		1" 25.4 mm	8" 203 mm	16" 406 mm	24" 609 mm	32" 812 mm	40" 1016 mm	56" 1422 mm	72" 1828 mm	90" 2286 mm	120" 3048 mm
TU Series	TU 200	0 – 200 mm (0 – 7.87")		→ Clamping capacity: 100 – 290 mm (3.94 – 7.87")							
	TU 400	0 – 400 mm (0 – 15.75")		→ Clamping capacity: 220 – 430 mm (8.66 – 16.93")							
	TU 600	0 – 600 mm (0 – 23.62")		→ Clamping capacity: 250 – 720 mm (9.84 – 28.35")							
	TU 1100	0 – 1100 mm (0 – 43.3")		→ Clamping capacity: 280 – 1210 mm (11.02 – 47.64")							
	TU 1200	0 – 1200 mm (0 – 47.2")		→ Clamping capacity: 280 – 1420 mm (11.02 – 55.91")							
	TU 1400	0 – 1400 mm (0 – 55.1")		→ Clamping capacity: 280 – 1440 mm (11.02 – 56.69")							
	TU 1800	0 – 1800 mm (0 – 70.8")		→ Clamping capacity: 836 – 2050 mm (32.91 – 80.71")							
	TU 2000	0 – 2000 mm (0 – 78.7")		→ Clamping capacity: 836 – 2250 mm (32.91 – 88.58")							
	TU 2400	0 – 2400 mm (0 – 94.5")		→ Clamping capacity: 836 – 2650 mm (32.91 – 104.33")							
	TU 2600	0 – 2600 mm (0 – 102.4")		→ Clamping capacity: 836 – 2850 mm (32.91 – 112.20")							
	TU 2800	0 – 2800 mm (0 – 110.2")		→ Clamping capacity: 836 – 3050 mm (32.91 – 120.08")							
	TU 3000	0 – 3000 mm (0 – 118.1")		→ Clamping capacity: 836 – 3250 mm (32.91 – 127.95")							
	TU 3200	0 – 3200 mm (0 – 125.9")		→ Clamping capacity: 836 – 3250 mm (32.91 – 135.83")							
XP Series	XP400NG	10 – 400 mm (0.39 – 15.7")		→ Clamping capacity: 180 – 460 mm (7.09 – 18.11")							
	XP600NG	10 – 600 mm (0.39 – 23.6")		→ Clamping capacity: 200 – 660 mm (7.87 – 25.98")							
	XP900NG	10 – 900 mm (0.39 – 35.433")		→ Clamping capacity: 290 – 990 mm (11.41 – 38.98")							
	XP1200	10 – 1200 mm (0.39 – 47.2")		→ Clamping capacity: 290 – 990 mm (11.41 – 38.98")							
	XP1800NG	10 – 1800 mm (0.39 – 70.8")		→ Clamping capacity: 836 – 2110 mm (32.91 – 83.07")							
	XP2000NG	10 – 2000 mm (0.39 – 78.74")		→ Clamping capacity: 836 – 2310 mm (32.91 – 90.94")							
	XP2200NG	10 – 2200 mm (0.39 – 86.6")		→ Clamping capacity: 836 – 2570 mm (32.91 – 101.18")							
	XP2400NG	10 – 2400 mm (0.39" – 94.5")		→ Clamping capacity: 836 – 2670 mm (32.91 – 104.33")							
	XP2600NG	10 – 2600 mm (0.39" – 102.4")		→ Clamping capacity: 836 – 2850 mm (32.91 – 112.20")							
	XP2800NG	10 – 2800 mm (0.39" – 110")		→ Clamping capacity: 836 – 3050 mm (32.91 – 120.08")							
	XP3000NG	10 – 3000 mm (0.39" – 118")		→ Clamping capacity: 836 – 3250 mm (32.91 – 127.95")							
XP3200NG	10 – 3200 mm (0.39" – 126")		→ Clamping capacity: 836 – 3450 mm (32.91 – 135.83")								
MS Series	MS600	0 – 600 mm (0" – 23.6")		→ Clamping capacity: 240 – 680 mm (9.45 – 26.77")							
	MS2300			1000 – 2300 mm (39.4" – 90.551") → Clamping capacity: 1250 – 2500 mm (49.21 – 98.43")							
TA 240	TA 240/100	0 – 200 mm (0" – 7.87")									
	TA 240/120	0 – 400 mm (0" – 15.7")									
	TA 240/170	0 – 600 mm (0" – 23.6")									
	TA 240/220	0 – 900 mm (0" – 35.4")									